

SmartID™ S10, SK10, SW100 and SWK100 Readers

ISO 14443 Reader or Reader/Writer

- ▶ Custom Configurations – Completely configurable for every access control application challenge.
- ▶ Open Architecture Design – ISO 14443A MIFARE®/ DESFire® Contactless smart card, compatible for broad card interoperability.
- ▶ Data Security – Secure data transmission with 3DES encryption.
- ▶ GSA-approved – Included in the U.S. General Services Administration (GSA) FIPS 201 Approved Product List.



ACCESS flexibility

The SmartID™ ISO 14443 reader is a flexible, highly secure and stylish contactless smart card reader ideal for customers that require a customizable reader for new or existing installations. Designed for a wide variety of applications from entry level access control to secure ID management, the reader family is completely configurable for every access control application challenge.

The SmartID™ reader offers the ultimate choice in interoperability and programmability. Its unique capabilities, such as reading any MIFARE® and/or DESFire® application data file, meet all installation requirements.

SmartID™ readers provide one of the broadest ranges of card compatibility in the industry and can be configured as a specific solution for each project (see specifications chart on opposite side for specific compatibilities). The SmartID™ reader is available with or without keypad, adding an extra layer of protection for higher security installations.

- ▶ Configuration cards can further personalize reader configurations to best match installation requirements.
- ▶ Wide voltage span (4.5-16 VDC).
- ▶ Wiegand or Clock-and-Data outputs easily interface with existing access control panels.
- ▶ Communications configurable to RS232, RS485 and RS422 for read only or read/write applications.

Features

Mounting The reader easily mounts on a door mullion or single-gang electrical box (using the electrical box cover plate accessories). An LED flashes green and the beeper sounds when reader is presented with MIFARE®, MIFARE DESFire® or other reader application compatible card. The multiple LEDs and beeper can also be controlled by the host system.

Security MIFARE® Contactless smart card and reader platform according to the ISO 14443A. The card structure provides multi-application functionality, whereby each application is secured for read and read/write by security keys. All RF data transmission between card and reader is encrypted using mutual authentication and challenge response to prevent replay attacks. Readers and cards must have matching security keys.

MIFARE DESFire® Contactless smart card and reader platform according to ISO 14443 level 4. Featuring DES and 3DES Encryption on all RF data

transmission. The card structure provides multi-application functionality, whereby each application is secured up to 14 different user-definable security keys for read and read/write access. Readers and cards must have matching security keys

Easily Interfaced

The SmartID™ provides flexible configurable output formats and output protocols. Reader communication supported: Wiegand, Clock-and-Data, ISO 7811 Clock-and-Data ABA Track 2 Emulation, RS232, RS422, RS485 or custom format output.

Indoor/Outdoor Design

Rugged, weatherized polycarbonate enclosure, designed to withstand harsh environments, provides reliable performance and resistance to vandalism.

* Base Model Numbers	800-8020 SmartID S10 MIFARE Mullion Reader (CSN Only) 800-8030 SmartID S10 MIFARE Mullion Reader 800-8030TC SmartID SW100 Reader/Writer (MIFARE, ISO14443-4 DESFire, SmartMX), T=CL Protocol 800-8062 SmartID S10 Dual MIFARE Mullion Reader 800-8061 SmartID S10 DESFire Mullion Reader 800-8080 SmartID S10 PIVII (FIPS 201 end-point compliant), GSA Approved, Reader 800-8045 SmartID SK10 MIFARE Mullion Keypad Reader 800-8045TC SmartID SWK100 Reader/Writer (MIFARE, ISO14443-4 DESFire, SmartMX), T=CL Protocol 800-8077 SmartID SK10 Dual MIFARE Mullion Keypad Reader 800-8076 SmartID SK10 DESFire Mullion Keypad Reader 800-8085 SmartID SK10 PIVII (FIPS 201 end-point compliant), GSA Approved, Keypad Reader
Dimensions	5.59" x 1.18" x 0.98" (14.2 x 4.6 x 2.5 cm)
Read Range	Up to 1.8" (4.6 cm) Dependent upon installation conditions.
Mounting	One of our smallest readers and ideally suited for mullion-mounted door installations, or any flat surface (Reader will not cover junction box). Optional single-gang electrical box mounting plate available. See 'Accessories' for more information.
Power Supply	4.5 – 16 VDC
Power Consumption	Average: 1.5 Watt Peak: 2.0 Watt
Operating Temperature	-4° F to 149° F (-20° C to 65° C)
Operating Humidity	0 – 95% non-condensing
Transmit Frequency	13.56 MHz
Applications	MIFARE (CSN), MIFARE (Sector), Dual MIFARE, DESFire, PIVII, T=CL (Read/Write)
Reader Outputs	Wiegand, Clock-and-Data, ISO7811 Clock-and-Data ABA Track 2 Emulation, RS232, RS485, RS422 or custom format output
Cable Distance	Wiegand/Clock-and-Data Interface 500 ft (150 m) (22AWG), RS232 50 ft (15 m), RS485/RS422 4000 ft (1220 m)
Card Compatibility	ISO 14443A * – read/write MIFARE, DESFire, SmartMX, US Government FIPS 201 * compatibility based on application selected
Certifications	UL 294/cUL***, FCC Certification, Canada Certification****, CE Mark (EU), Australia C-Tick, New Zealand, RoHS Compliant
Housing	SB TSG Polymers
Color	Silver
Accessories	500-8090 Single-gang electrical box mounting plate 500-9287 Wall mounting spacer 800-0300 Reader Tamper
Termination	Terminal Strip
Warranty	Warranted against defects in materials and workmanship for two years. (See complete warranty policy for details.)

* Additional custom configuration format is required to accompany all reader orders. Contact customer service for more information.

** Dependant upon installation conditions.

*** Models 800-8045 and 800-8084 are not UL certified

**** Limited models are Canada certified. Check with customer service for more details.

© 2008 HID Global. All rights reserved. HID, the HID logo, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 3/11/08 MKT-SmartID_S10_SK10_DS_EN



ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: 800 237 7769
Phone: +1 949 598 1600
Fax: 949 598 1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160 9800
Fax: +852 3160 4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840