

Product Specification

D series Access Control Readers Biometrics	MODEL	D7	D7K	
	MOUNTING	WALL PLATE PROVIDED	WALL PLATE PROVIDED	
	DIMENSIONS	79x128x18mm (3.1x5.0x0.7")	79x148x18mm (3.1x5.8x0.7")	

The D Series incorporates our access control card reader with keypad and fingerprint reader technologies. The hardware has an environmental rating of IP65 and is suitable for outdoor use. The enclosure is mounted in a semi-recessed fashion, providing a low profile biometric solution. The series is compatible with a range of contactless card technologies including Mifare and DESFire EV1. The electronics are fully encapsulated providing superior ingress protection and durability. Output data format is Wiegand or RS485 encrypted (model dependant).

CREDENTIAL		MIFARE		DESFIRE EV1		
CARD TYPE	MIF	FARE type A : ISO14443	DESFIRE EV1 : ISO14443			
READ RANGE		TYPICAL : 5cm	TYPICAL : 4cm			
KEYPAD (D7K)	3X4 WITH BACKLIGHT VARIOUS OUTPUTS AVAILABLE					
FINGERPRINT SENSOR	SAFRAN MORPHO OPTICAL FINGER SCANNER					
TRANSMIT FREQUENCY	13.56MHz					
OUTPUT PROTOCOL	WIEGAND : 26 BIT AS STANDARD OR CUSTOMER SPECIFIED FORMAT RS485 ENCRYPTED (AES-128BIT) COMMUNICATIONS					
VOLTAGE SUPPLY	+9VDC TO +24VDC					
CURRENT	320mA (ACTIVE AT 12VDC)					
STATUS LED	BI-COLOUR LED : RED / GREEN					
AUDIBLE TONE	BUZZER					
CABLE DISTANCE	WIEGAND: 150m (500ft): 22 AWG WIRE RS485: 1000m (3200ft): 22 AWG WIRE					
OPERATING TEMPERATURE	-10degC TO +55degC					
RELATIVE HUMIDITY	90% MAX : OPERATIONAL NON-CONDENSING					
ENCLOSURE MATERIAL	ALUMINIUM SHROUD : HIGH IMPACT POLYCARBONATE					
COLOUR	SILVER / CHARCOAL					
IP RATING	IP 65					
CERTIFICATIONS	FCC : CE : C-TICK					
WARRANTY	1 YEAR					
PART NUMBERS	D7-M	MIFARE READER FINGERPRINT SCANNER	D7-EV1	DESFIRE EV1 READER FINGERPRINT SCANNER		
	D7K-M	MIFARE READER FINGERPRINT SCANNER KEYPAD	D7K-EV1	DESFIRE EV1 READER FINGERPRINT SCANNER KEYPAD	INS-SPEC-D7X-0	

CONTACT

INS GLOBAL PTY LTD SUITE 8, 166A THE ENTRANCE RD ERINA, NSW 2250 AUSTRALIA





